

Bicotest PowerPal

Multi-attachment 240V lead

Data Sheet

- RCD protection
- Retractable cable webbing to allow leads of any required length
- Various attachments for all connection needs
- Order code: 64598801



Description

The PowerPal is a multi attachment 240V power lead which can be used to provide a safe 240V supply in a variety of situations where needed e.g. from busbars and street lighting.

The PowerPal is made up of an IP54 rated single socket which is connected to an in-line 30mA RCD device and is terminated to 10A fuse holders. Various attachments can be connected to the fuseholders depending on your needs: 4mm plugs, crocodile clips or

Specification

Rated voltage :	240 Vac @50 Hz
Max current :	10A
In-line fuse :	32mm F10A 600V
Rated trip current :	30mA
Trip speed (typical) :	40 milliseconds
Protection rating :	IP54
Safety :	BS7071: 1992, BS1363-2, GS38 compliant
Temperature rating :	-10°C to 150°C



Leaders in Utility Instrumentation

Bicotest Ltd,
Hellesdon Park Road,
Drayton High Road,
Norwich,
UK, NR6 5DR

Tel + 44 (0) 1603 416 900
Fax + 44 (0) 1603 416 902
enquiries@bicotest.co.uk
www.bicotest.co.uk